

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 5970 (1970): Method for estimation of strength (vat content) of solubilized vat dyestuffs [TXD 7: Textile Sizing and Finishing Materials]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



Indian Standard
METHOD FOR ESTIMATION
OF STRENGTH (VAT CONTENT) OF
SOLUBILIZED VAT DYESTUFFS

(First Reprint JUNE 1989)

UDC 677.016.424

© Copyright 1971

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Indian Standard

METHOD FOR ESTIMATION OF STRENGTH (VAT CONTENT) OF

Dyestuffs Sectional Committee, TDC 38

Chairman

SHRI B. V. SHAH

Representing

The Atul Products Limited, Atul

Members

SHRI B. M. BRAHME (<i>Alternate to</i> Shri B. V. Shah)	
SHRI C. R. ASNANI	The Century Spinning & Weaving Co Ltd, Bombay
SHRI D. R. SHARMA (<i>Alternate</i>)	
SHRI K. S. BHARGAVA	Rohtas Industries Ltd, Dalmianagar
SHRI B. V. BHATT	The Ahmedabad Manufacturing & Calico Printing Co Ltd, Ahmedabad
SHRI K. G. SHAH (<i>Alternate</i>)	
SHRI S. K. BOSE	National Test House, Calcutta
DR S. CHATTERJEE	Suhrid Geigy Trading Limited, Bombay
SHRI R. N. WADIA (<i>Alternate</i>)	
SHRI N. H. DESAI	Ahmedabad Textile Industry's Research Association, Ahmedabad
DR R. D. DESAI	M. G. Science Institute, Ahmedabad
SHRI K. M. GANDHI	I. C. I. (India) Private Limited, Calcutta
DR B. M. PATEL (<i>Alternate</i>)	
SHRI JOGINDER SINGH	Directorate General of Technical Development, New Delhi
SHRI V. S. KANKARE	Wool Research Association, Bombay
SHRI H. C. KHATIWALA	Arlabs Limited, Bombay
DR C. B. KOTHARI	The Textile Association (India) Regd, Ahmedabad
SHRI T. A. SUBRAMANYAM (<i>Alternate</i>)	
DR A. Y. KULKARNI	Indian Jute Industries' Research Association, Calcutta
SHRI G. A. KULKARNI	Amar Dye-Chem Ltd, Bombay
SHRI S. V. DESAI (<i>Alternate</i>)	
DR G. G. KULKARNI	Chika Limited, Bombay
SHRI S. T. CHARI (<i>Alternate</i>)	
SHRI P. S. NADKARNI	Ministry of Defence (R & D)
SHRI M. G. BHARGAVA (<i>Alternate</i>)	
DR K. I. NARASIMHAN	Office of the Textile Commissioner, Bombay
SHRI K. S. BHUJANG (<i>Alternate</i>)	
DR M. V. NIMKAR	The Millowners' Association, Bombay

(Continued on page 2)

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

(Continued from page 1)

<i>Members</i>	<i>Representing</i>
SHRI RAJENDRA SHANKAR	Indian Dyestuff Industries Ltd, Bombay
SHRI S. G. PARULKAR (<i>Alternate</i>)	
SHRI R. RAMAKRISHNAN	The Bangalore Woollen, Cotton & Silk Mills Co Ltd, Bangalore; and The Buckingham & Carnatic Co Ltd, Madras
DR J. M. RANE	Hickson & Dadajee Ltd, Bombay
SHRI H. V. DHARWARKAR (<i>Alternate</i>)	
SHRI M. N. RAO	The Indian Paint Association, Calcutta
SHRI N. S. BHARTIA (<i>Alternate</i>)	
SHRI SANTOKH SINGH	National Chemical Industries, New Delhi
SHRI N. S. SARAIYA	The Bombay Textile Research Association, Bombay
SHRI K. A. SHAH	The Sarangpur Cotton Manufacturing Co Ltd, Ahmedabad
SHRI K. V. SHENOY	Ciba of India Ltd, Bombay
SHRI T. SADASIVAN (<i>Alternate</i>)	
SHRI S. M. CHAKRABORTY, Director (Tex)	Director General, ISI (<i>Ex-officio Member</i>)

Secretary
SHRI D. R. KOHLI
Assistant Director (Tex), ISI

Vat Dyes Subcommittee, TDC 38 : 2

<i>Convener</i>	
SHRI K. S. BHUJANG	Office of the Textile Commissioner, Bombay
<i>Members</i>	
SHRI B. M. BRAHME	Atic Industries Limited, Atul
SHRI S. R. IYER (<i>Alternate</i>)	
SHRI H. C. KHATIWALA	Arlabs Limited, Bombay
DR M. V. NIMKAR	Bombay Dyeing & Manufacturing Company Limited, Bombay
SHRI S. G. PARULKAR	Indian Dyestuff Industries Ltd, Bombay
SHRI R. NARAYANAN (<i>Alternate</i>)	
SHRI SANTOKH SINGH	National Chemical Industries, New Delhi

Indian Standard

METHOD FOR ESTIMATION OF STRENGTH (VAT CONTENT) OF SOLUBILIZED VAT DYESTUFFS

0. FOREWORD

0.1 This Indian Standard was adopted by the Indian Standards Institution on 30 November 1970, after the draft finalized by the Dyestuffs Sectional Committee had been approved by the Textile Division Council.

0.2 Solubilized vat dyestuffs are increasingly being used in the industry for dyeing and printing of fabrics. The strength of solubilized vat dyes is generally determined by comparison with an agreed standard by dyeing test which creates difficulties in reporting records of production, import or export statistics, or comparing dyes where due to slight shade difference the assessment of strength by dyeing method becomes difficult. To overcome this difficulty, this standard has been prepared to determine the strength by gravimetric method which agrees with the dyeing tests. The method prescribed is applicable to individual dyes but not to a mixture of dyes. It takes care of dyes which are precipitated due to over oxidation. However, it may not be very much suitable for dyes which are partially oxidized and pass through the filtering media.

0.3 In reporting the result of a test or analysis made in accordance with this standard, if the final value, observed or calculated, is to be rounded off, it shall be done in accordance with IS : 2-1960*.

1. SCOPE

1.1 This standard prescribes a gravimetric method for the estimation of strength (vat content) of homogeneous solubilized vat dyestuffs.

2. SAMPLING

2.1 All the containers of the dyestuffs of same designation and strength delivered to a buyer against a despatch note shall constitute a lot.

*Rules for rounding off numerical values (*revised*).

2.2 Unless otherwise agreed to between the buyer and the seller, the number of containers to be selected at random from the lot shall be as given below:

<i>Lot Size</i>	<i>Sample Size</i>
Up to 25	2
26 to 50	3
51 „ 150	5
151 and above	7

2.3 Draw small quantities of dye by suitable sampling instrument from at least 3 different parts of each container and mix them thoroughly to get a composite sample of desired weight.

3. APPARATUS AND REAGENTS

3.1 Sintered Glass Funnel and Crucible — porosity G 4.

3.2 Distilled Water — See IS : 1070-1960*.

3.3 Sodium Nitrite Solution — 10 percent (*w/v*).

3.4 Dilute Sulphuric Acid — prepared by diluting 10 ml of concentrated sulphuric acid to 100 ml.

NOTE — Unless specified otherwise, pure chemicals shall be used in the tests. 'Pure chemicals' shall mean chemicals that do not contain impurities which affect the test results.

4. PROCEDURE

4.1 Take about 2 g of solubilized vat dyestuff and weigh it accurately. Dissolve the dyestuff in 200 ml of distilled water at 60°C. Filter the solution while hot through sintered glass funnel of porosity G4 type and wash the funnel with hot distilled water until the dissolved dyestuff goes into the filtrate.

4.2 Add 10 ml of sodium nitrite solution and 10 ml of dilute sulphuric acid to the solution obtained as in 4.1. Boil for 5 minutes and filter it through a previously weighed sintered glass crucible of porosity G4 type. Wash the residue on the crucible with distilled water till free from acid using an appropriate indicator, such as bromocresol purple. Dry the crucible along with the residue at $100 \pm 3^\circ\text{C}$ to constant weight. Determine the weight of the residue.

4.3 Repeat the test with at least two more test specimens.

*Specification for water, distilled quality (*revised*).

5. CALCULATIONS

5.1 Calculate the strength of the solubilized vat dyestuff by the following formula:

$$P = \frac{W_2}{W_1} \times 100$$

where

P = percentage by weight of the vat content of solubilized vat dyestuff,

W_2 = weight in g of the residue obtained as in 4.2, and

W_1 = weight in g of the solubilized vat dyestuff taken for the test (see 4.1).

5.2 Similarly, calculate the strength of the other test specimens and calculate the average of the results.

6. REPORT

6.1 The report shall include the following:

- a) Strength of dyestuff, and
- b) Number of tests.

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones: 331 01 31, 331 13 75

Telegrams: Manaksanstha
(Common to all Offices)

Regional Offices:

	Telephone
Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002	{ 331 01 31 331 13 75
*Eastern : 1/14 C. I. T. Scheme VII M, V. I. P. Road, Maniktola, CALCUTTA 700054	36 24 99
Northern : SCO 445-446, Sector 35-C, CHANDIGARH 160036	{ 2 18 43 3 16 41
Southern : C. I. T. Campus, MADRAS 600113	{ 41 24 42 41 25 19 41 29 16
†Western : Manakalaya, E9 MIDC, Marol, Andheri (East), BOMBAY 400093	6 32 92 95

Branch Offices:

'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMADABAD 380001	{ 2 63 48 2 63 49
†Peenya Industrial Area 1st Stage, Bangalore Tumkur Road BANGALORE 560058	{ 38 49 55 38 49 56
Gangotri Complex, 5th Floor, Bhadbhada Road, T. T. Nagar, BHOPAL 462003	6 67 16
Plot No. 82/83, Lewis Road, BHUBANESHWAR 751002	5 36 27
53/5, Ward No. 29, R.G. Barua Road, 5th Byelane, GUWAHATI 781003	3 31 77
5-8-56C L. N. Gupta Marg (Nampally Station Road) HYDERABAD 500001	23 10 83
R14 Yudhister Marg, C Scheme, JAIPUR 302005	{ 6 34 71 6 98 32
117/418 B Sarvodaya Nagar, KANPUR 208005	{ 21 68 76 21 82 92
Patliputra Industrial Estate, PATNA 800013	6 23 05
T.C. No. 14/1421, University P.O., Palayam TRIVANDRUM 695035	{ 6 21 04 6 21 17

Inspection Offices (With Sale Point):

Pushpanjali, First Floor, 205-A West High Court Road, Shankar Nagar Square, NAGPUR 440010	2 51 71
Institution of Engineers (India) Building, 1332 Shivaji Nagar, PUNE 411005	5 24 35

*Sales Office in Calcutta is at 5 Chowringhee Approach, P. O. Princep Street, Calcutta 700072

†Sales Office in Bombay is at Novelty Chambers, Grant Road, Bombay 400007

†Sales Office in Bangalore is at Unity Building, Narasimharaja Square, Bangalore 560002

Reprography Unit, BIS, New Delhi, India